



Fire Retardant Coatings of Texas®, LLC

1150 Blue Mound Rd West #403
Haslet, Texas 76052 Office (817) 710-5233
www.frctexas.com

Safety Data Sheet (SDS)

Printing date 3/18/2016

OSHA Hazard Communication Standard 29 CFR 1910.1200.
Prepared to GHS Rev04.


Reviewed on 3/18/2016

1 Product and Company Identification

- **Product identifier**
- **Trade name:** **FX Lumber Guard XT®**
- **Article number:** FX Lumber Guard XT®
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Product description**
Fire retardant product for exterior / interior lumber & plywood (SYP, SPF, oak, cedar, red oak, Fir and similar), timbers, shake shingles, thatching, bamboo and similar other materials.
Non Hazardous Penetrant – Non Toxic – Environment Safe – Water Based
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Fire Retardant Coatings of Texas®, LLC
1150 Blue Mound Rd West #403
Haslet, TX 76052
Off (817) 710-5233
Fax (817) 439-8385
- **Emergency telephone number:** (817) 710-5233

2 Hazards identification

- **Classification of the substance or mixture**
The product is not classified according to the Globally Harmonized System (GHS).
- **Label elements**
- **GHS label elements** Void
- **Hazard pictograms** Void
- **Signal word** Void
- **Hazard statements** Void
- **Precautionary statements** Precautionary statements
- **Classification system:** NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme
- **NFPA ratings (scale 0 - 4)**



Health = 0
Fire = 0
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



HEALTH 0 Health = 0
FIRE 0 Fire = 0
REACTIVITY 0 Reactivity = 0

Other hazards

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

461-58-5	dicyandiamide	<9%
7732-18-5	water, distilled, conductivity or of similar purity	<86%
7783-28-0	diammonium phosphate	<4%

- **Chemical characterization:** Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.



Fire Retardant Coatings of Texas®, LLC

1150 Blue Mound Rd West #403
Haslet, Texas 76052 Office (817) 710-5233
www.frctexas.com

Safety Data Sheet (SDS)

Printing date 3/18/2016

OSHA Hazard Communication Standard 29 CFR 1910.1200.

Reviewed on 3/18/2016

Trade name:

Prepared to GHS Rev04.

FX LumberGuard XT®

(Contd. of page 1)

· Dangerous components:			
7664-38-2	phosphoric acid 75%	H314	<10%
57-13-6	urea		≤2%

4 First aid measures

- **Description of first aid measures**
- **General information:** No special measures required.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Wash affected area with soap and water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Give large amounts of water. If symptoms persist consult doctor.
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures:** Required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **Reference to other sections**
No dangerous substances are released.
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling** No special measures required.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 3)



Fire Retardant Coatings of Texas®, LLC

1150 Blue Mound Rd West #403
Haslet, Texas 76052 Office (817) 710-5233
www.frctexas.com

Safety Data Sheet (SDS)

Printing date 3/18/2016

OSHA Hazard Communication Standard 29 CFR 1910.1200.
Prepared to GHS Rev04.

Reviewed on 3/18/2016

Trade name:

FX LumberGuard XT®

(Contd. of page 2)

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

7664-38-2 phosphoric acid 85%	
PEL	1 mg/m ³
REL	Short-term value: 3 mg/m ³ Long-term value: 1 mg/m ³
TLV	Short-term value: 3 mg/m ³ Long-term value: 1 mg/m ³
57-13-6 urea	
WEEL	10 mg/m ³

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:** Recommended when handling any chemicals.

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

· **Breathing equipment:** Not required.

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can't be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Goggles recommended during refilling.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Clear

· **Odor:** Yes

· **Odor threshold:** Slight

· **PH Range:** 4.5-5%

· **Change in condition**

Freeze Point: <40°

Boiling point/Boiling range: 212 °F

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not applicable.

(Contd. on page 4)



Fire Retardant Coatings of Texas®, LLC

1150 Blue Mound Rd West #403
Haslet, Texas 76052 Office (817) 710-5233
www.frctexas.com

Page 4/7

Safety Data Sheet (SDS)

Printing date 3/18/2016

OSHA Hazard Communication Standard 29 CFR 1910.1200.
Prepared to GHS Rev04.

Reviewed on 3/18/2016

Trade name:

FX LumberGuard XT®

(Contd. of page 3)

- **Ignition temperature:**
 - **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not self-igniting.
- **Danger of explosion:** Product does not present an explosion hazard.
- **Explosion limits:**
 - **Lower:** Not determined.
 - **Upper:** Not determined.
- **Vapor pressure at 20 °C (68 °F):** 23 hPa (17 mm Hg)
- **Density:** SG 1.020
- **Relative density:** Not determined.
- **Vapor density:** Not determined.
- **Evaporation rate:** Not determined.
- **Solubility in / Miscibility with Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - **Dynamic:** Not determined.
 - **Kinematic:** Not determined.
- **Solvent content:**
 - **Organic solvents:** 0.0 %
 - **Water:** <86 %
- **Solids content:** 32 %
- **VOC Content:** 0.06%

10 Stability and reactivity

- **Reactivity:** None
- **Chemical stability:** Stable
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:** Not to mixed with any other chemicals.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:** Non Toxic
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Slight
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product is not subject to classification according to internally approved calculation methods for preparations:

(Contd. on page 5)



Fire Retardant Coatings of Texas®, LLC

1150 Blue Mound Rd West #403
Haslet, Texas 76052 Office (817) 710-5233
www.frctexas.com

Safety Data Sheet (SDS)

Printing date 3/18/2016

OSHA Hazard Communication Standard 29 CFR 1910.1200.

Reviewed on 3/18/2016

Trade name:

Prepared to GHS Rev04.

FX LumberGuard XT®

(Contd. of page 4)

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)
None of the ingredients is listed.
· NTP (National Toxicology Program)
None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Smaller quantities can be disposed of with household waste.
- **Uncleansed Packaging's:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, ADN, IMDG, IATA** Void
- **UN proper shipping name** None
- **DOT, ADR, ADN, IMDG, IATA** Void
- **Transport hazard class(es)** TM
- **DOT, ADR, ADN, IMDG, IATA**
- **Class** Void
- **Packing group**
- **DOT, ADR, IMDG, IATA** Void
- **Environmental hazards:**
- **Marine pollutant:** No
- **Special precautions for user** Not applicable.
- **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.
- **UN "Model Regulation":** -

(Contd. on page 6)



Fire Retardant Coatings of Texas®, LLC

1150 Blue Mound Rd West #403
Haslet, Texas 76052 Office (817) 710-5233
www.frctexas.com

Safety Data Sheet (SDS)

Printing date 3/18/2016

OSHA Hazard Communication Standard 29 CFR 1910.1200.
Prepared to GHS Rev04.

Reviewed on 3/18/2016

Trade name:

FX LumberGuard XT®

(Contd. of page 5)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

• **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

• **Section 313 (Specific toxic chemical listings):**

7664-38-2 phosphoric acid 85%

• **TSCA (Toxic Substances Control Act):**

461-58-5 dicyandiamide

7664-38-2 phosphoric acid 85%

57-13-6 urea

7732-18-5 water, distilled, conductivity or of similar purity

• **Proposition 65**

• **Chemicals known to cause cancer:**

None of the ingredients is listed.

• **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

• **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

• **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

• **Carcinogenic categories**

• **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

• **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

• **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

• **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

• **GHS label elements** Void

• **Hazard pictograms** Void

• **Signal word** Void

• **Hazard statements** Void

• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 7)



Fire Retardant Coatings of Texas®, LLC

1150 Blue Mound Rd West #403
Haslet, Texas 76052 Office (817) 710-5233
www.frctexas.com

Page 7/7

Safety Data Sheet (SDS)

Printing date 3/18/2016

OSHA Hazard Communication Standard 29 CFR 1910.1200.
Prepared to GHS Rev04.

Reviewed on 3/18/2016

Trade name:

FX LumberGuard XT®

(Contd. of page 6)

DOT: US Department of Transportation IATA:
International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
SDS / MSDS Created by MSDS Authoring Services (www.MSDSAuthoring.com)

DISCLAIMER

The information in this document is believed to be correct as of the date issued.

HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE.

This information and the product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk of his use thereof.

