



Fire Retardant Coatings of Texas®, LLC
 4500 Grants Lane · Fort Worth, TX 76179
 Office (817) 710-5233 · www.frctexas.com



FX FabricGuard

TECHNICAL DATA SUBMITTAL SHEET

Interior Fire Retardant Spray is for cotton, cotton/polyester, denim, canvas, and Terry Cloth. Artificial Silk Foliage, Décor, Wall Tapestries, Window Shades (non-element contact). Canopies, etc.

NON TOXIC	ENVIRONMENT SAFE	Low VOC Content & Emissions	NON- CORROSIVE
PH: 5.5	Shelf Life 3 yrs stored <125°	ONE APPLICATION	Viscosity 1.06
350-400 sf per gal	DO NOT DILUTE	DON'T LET IT FREEZE	TRANSPARENT
Apply Temperature Range: 45°F - 95°F		Class A FR (E84)	NON-HAZMAT

Testing

California State Fire Marshal Test 1237.1 • NFPA 701 • CAN/ULC S109-03 • Fed. Motor Vehicle Safety Standard 302 • ASTM E84 (UL723) CLASS A FIRE RETARDANT

Meets 16 CFR 1500.3 Federal Hazardous Substances Act (FHSA) of the Consumer Product Safety Commission (CPSC) & FDNY requirements

NOT FOR CLOTHING OR BEDDING BECAUSE IT MAY CAUSE SKIN IRRITATION

Application Process:

The material to be treated must be clean & dry before treatment. Agitate product before and during application. Apply **FX FabricGuard** as it's received. Apply by spraying with a low-pressure hand pump sprayer at a rate of 350-400 sf per gallon, or use a sponge to dampen the fabric. Apply until damp, as the fabric will absorb the fire retardant. Drying time will vary from 4 to 12 hours depending on weather, fabric density, and humidity. Clean up with soap & water.

Cleaning / Retreating:

Your fire-retardant-treated fabric can be dry-cleaned (dry-chemicals only) as recommended by the fabric manufacturer. However, once the treated fabric has been cleaned 2-3 times, it will need to be retreated. Typically, the flame-retardant performance of topically treated fabric is certified for 3 years under handling or cleaning conditions. However, the actual duration the treatment remains effective will vary depending on how often it is cleaned and handled, as well as environmental conditions.

Treated fabric (floor coverings/wall coverings) that isn't dry-cleaned does not require retreatment.

Warranty: Please visit www.frctexas.com for warranty information



WARNING: KEEP THIS AND ALL CHEMICALS OUT OF CHILDRENS REACH AS WITH ANY PRODUCT, THIS PRODUCT MAY CAUSE EYE AND/OR SKIN IRRITATION - ALWAYS WEAR PERSONAL PROTECTION EQUIPMENT WHEN HANDLING THIS OR ANY CHEMICALS