



# Fire Retardant Coatings of Texas®, LLC

1150 Blue Mound Rd West #403  
Haslet, Texas 76052  
Office (817) 710-5233 Fax (817) 439-8385  
www.frctexas.com



CALIFORNIA  
REGISTERED  
C-25901

## FX FabricGuard

## SUBMITTAL SHEET

Interior Fire Retardant Spray for cotton, cotton/polyester, denim, Canvas and Terry Cloth. Artificial Silk Foliage, Décor, Wall Tapestries, Window Shades, etc.  
Limited exterior use (NON-ELEMENT CONTACT).

|                        |                                  |                             |                         |
|------------------------|----------------------------------|-----------------------------|-------------------------|
| NON TOXIC              | ENVIRONMENT SAFE                 |                             | NON CORROSIVE           |
| PH Range:<br>4.5 – 5 % | Shelf Life 3 yrs<br>stored <125° | ONE COAT<br>APPLICATION     | Anti-Bacterial:<br>Good |
| 350-400 sf<br>per gal  | <b>DO NOT<br/>DILUTE</b>         | <b>DON'T LET<br/>FREEZE</b> | TRANSPARENT             |

Meets 16 CFR 1500.3 Federal Hazardous Substances Act (FHSA) of the Consumer Product Safety Commission (CPSC)

### Testing

California State Fire Marshal Test 1237.1 • NFPA 701 • CAN/ULC S109-03  
Federal Motor Vehicle Safety Standard 302  
ASTM E84 (UL723) CLASS A FIRE RETARDANT

**NOT RECOMMENDED FOR CLOTHING OR BEDDING, DUE TO IT MAY CAUSE SKIN IRRITATION**

### Application Process:

Material to be treated must be clean & dry before treating. Agitate product before and during application. Apply **FX FabricGuard** as it's received. Apply by spraying with a low pressure hand pump sprayer at a rate of 350 / 400 sf per gallon or you can use a sponge to dampen the fabric. Apply until damp as the fabric will absorb the fire retardant. Drying time will vary 4-12hrs depending on weather, density of fabric and humidity. Clean up with soap & water.

### Cleaning / Retreating:

Your fire retardant treated fabric can be dry-cleaned (dry chemicals only) as recommended by the fabric manufacturer, however, once the treated fabric has been cleaned 3-4 times it will need to be retreated. Typically, the flame retardancy of topically treated fabric is certified depending on handling or cleaning for 3 years, though the actual length of time in which the treatment remains effective will vary based on the number of times it is cleaned, handled and/or environmental conditions.

**Treated Fabric (floor coverings / wall coverings) that aren't dry cleaned do not require retreatment.**

Warranty: Please visit [www.frctexas.com](http://www.frctexas.com) for warranty information



**WARNING: KEEP THIS AND ALL CHEMICALS OUT OF CHILDRENS REACH  
AS WITH ANY PRODUCT, THIS PRODUCT MAY CAUSE EYE AND/OR SKIN IRRITATION - ALWAYS WEAR PERSONAL PROTECTION EQUIPMENT WHEN HANDLING THIS OR ANY CHEMICALS**