



Fire Retardant Coatings of Texas®, LLC

1150 Blue Mound Rd West #403
Haslet, Texas 76052 Office (817) 710-5233
Sales@frctexas.com • www.frctexas.com

Safety Data Sheet (SDS)

Printing date 03/18/2016

OSHA Hazard Communication Standard 29 CFR 1910.1200.
Prepared to GHS Rev04.

Reviewed on April 2019

1 Product and Company Identification

- **Product identifier**
- **Trade name:** **FX LumberGuard®**
- **Article number:** **FX LumberGuard®**
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Product description**
Fire retardant for interior lumber, plywood, OSB and I-Joist.
Non-Hazardous Penetrant – Non-Toxic – Environment Safe – Water Based
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Fire Retardant Coatings of Texas®, LLC
1150 Blue Mound Rd West #403
Haslet, TX 76052
Off (817) 710-5233 Fax (817) 439-8385
- **Emergency telephone number:** (817) 710-5233
- **“Fire Retardant Coatings of Texas”, “FX Lumber Guard / FX Lumber Guard XT”**
- **& “FRCT” Logo are federally registered trademarks**



2 Hazards identification

- **Classification of the substance or mixture**
The product is not classified according to the Globally Harmonized System (GHS).
- **Label elements**
- **GHS label elements** Void
- **Hazard pictograms** Void
- **Signal word** Void
- **Hazard statements** Void
- **Precautionary statements** Precautionary statements
- **Classification system:** NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme
- **NFPA ratings (scale 0 - 4)**



Health = 0
Fire = 0
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = 0
Fire = 0
Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

461-58-5	dicyandiamide	<4%
7732-18-5	water, distilled, conductivity or of similar purity	<85%
7783-28-0	diammonium phosphate	<2%

- **Chemical characterization:** **Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.



Safety Data Sheet (SDS)

Printing date 03/18/2016

OSHA Hazard Communication Standard 29 CFR 1910.1200.
Prepared to GHS Rev04.

Reviewed on April 2019

Trade name:

FX LumberGuard®

(Contd. of page 1)

· Dangerous components:			
7664-38-2	Phosphoric Acid 75% Food Grade	H314	<2.5%
57-13-6	Urea Prills		2%
	Proprietary		4.5%

4 First aid measures

- **Description of first aid measures**
- **General information:** No special measures required.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Wash effective area with soap and water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Give large amounts of water. If symptoms persist consult doctor.
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **Reference to other sections**
No dangerous substances are released.
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling** No special measures required.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 3)



Fire Retardant Coatings of Texas, LLC

1150 Blue Mound Rd West #403
Haslet, Texas 76052 Office (817) 710-5233
Sales@frctexas.com • www.frctexas.com

Safety Data Sheet (SDS)

Printing date 03/18/2016

OSHA Hazard Communication Standard 29 CFR 1910.1200.
Prepared to GHS Rev04.

Reviewed on April 2019

Trade name:

FX LumberGuard®

(Contd. of page 2)

• **Control parameters**

• **Components with limit values that require monitoring at the workplace:**

7664-38-2 phosphoric acid 75% Food Grade

PEL	1 mg/m ³
REL	Short-term value: 3 mg/m ³ Long-term value: 1 mg/m ³
TLV	Short-term value: 3 mg/m ³ Long-term value: 1 mg/m ³

57-13-6 urea

WEEL	10 mg/m ³
------	----------------------

• **Additional information:** The lists that were valid during the creation were used as basis.

• **Exposure controls**

• **Personal protective equipment:**

• **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

• **Breathing equipment:** Not required.

• **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can't be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **Eye protection:** Goggles recommended during refilling.

9 Physical and chemical properties

• **Information on basic physical and chemical properties**

• **General Information**

• **Appearance:**

Form: Liquid

Color: Cloudy

• **Odor:** Yes

• **Odor threshold:** Slight

• **pH-value range:** 5.5 – 7 %

• **Change in condition**

Freezing point/Freezing range : <40 °F

Boiling point/Boiling range: >212 °F

• **Flash point:** Not applicable.

• **Flammability (solid, gaseous):** Not applicable.

(Contd. on page 4)



Fire Retardant Coatings of Texas, LLC

1150 Blue Mound Rd West #403
Haslet, Texas 76052 Office (817) 710-5233
Sales@frctexas.com • www.frctexas.com

Page 4/7

Safety Data Sheet (SDS)

Printing date 03/18/2016

OSHA Hazard Communication Standard 29 CFR 1910.1200.
Prepared to GHS Rev04.

Reviewed on April 2019

Trade name:

FX LumberGuard®

(Contd. of page 3)

- **Ignition temperature:**
 - **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not self-igniting.
- **Danger of explosion:** Product does not present an explosion hazard.
- **Explosion limits:**
 - **Lower:** Not determined.
 - **Upper:** Not determined.
- **Vapor pressure at 20 °C (68 °F):** 23 hPa (17 mm Hg)
- **Density:** SG 1.020%
- **Relative density:** Not determined.
- **Vapour density:** Not determined.
- **Evaporation rate:** Not determined.
- **Solubility in / Miscibility with Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - **Dynamic:** Not determined.
 - **Kinematic:** Not determined.
- **Solvent content:**
 - **Organic solvents:** 0.0 %
 - **Water:** 85 %
- **Solids content:** 32 %
- **Other information:** No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
 - **on the skin:** No irritant effect.
 - **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product is not subject to classification according to internally approved calculation methods for preparations:

(Contd. on page 5)



Fire Retardant Coatings of Texas, LLC

1150 Blue Mound Rd West #403
Haslet, Texas 76052 Office (817) 710-5233
Sales@frctexas.com • www.frctexas.com

Safety Data Sheet (SDS)

Printing date 03/18/2016

OSHA Hazard Communication Standard 29 CFR 1910.1200.

Reviewed on April 2019

Trade name:

FX LumberGuard®

Prepared to GHS Rev04.

(Contd. of page 4)

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)
None of the ingredients is listed.
· NTP (National Toxicology Program)
None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Bio accumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Smaller quantities can be disposed of with household waste.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, ADN, IMDG, IATA** Void
- **UN proper shipping name** None
- **DOT, ADR, ADN, IMDG, IATA** Void
- **Transport hazard class(es)** TM
- **DOT, ADR, ADN, IMDG, IATA**
- **Class** Void
- **Packing group**
- **DOT, ADR, IMDG, IATA** Void
- **Environmental hazards:**
- **Marine pollutant:** No
- **Special precautions for user** Not applicable.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- **UN "Model Regulation":** -

(Contd. on page 6)



Fire Retardant Coatings of Texas, LLC

1150 Blue Mound Rd West #403
Haslet, Texas 76052 Office (817) 710-5233
Sales@frctexas.com • www.frctexas.com

Safety Data Sheet (SDS)

Printing date 03/18/2016

OSHA Hazard Communication Standard 29 CFR 1910.1200.
Prepared to GHS Rev04.

Reviewed on April 2019

Trade name:

FX LumberGuard®

(Contd. of page 5)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

• **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

• **Section 313 (Specific toxic chemical listings):**

7664-38-2 phosphoric acid 75% food grade

• **TSCA (Toxic Substances Control Act):**

461-58-5 dicyandiamide

7664-38-2 phosphoric acid 75% food grade

57-13-6 Urea Prills

7783-28-0 diammonium phosphate

7732-18-5 water, distilled, conductivity or of similar purity

• **Proposition 65**

• **Chemicals known to cause cancer:**

None of the ingredients is listed.

• **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

• **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

• **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

• **Carcinogenic categories**

• **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

• **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

• **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

• **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

• **GHS label elements** Void

• **Hazard pictograms** Void

• **Signal word** Void

• **Hazard statements** Void

• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Abbreviations and acronyms:**

ADR: Accord European sur le transport des marchandises danger uses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods



Fire Retardant Coatings of Texas, LLC

1150 Blue Mound Rd West #403
Haslet, Texas 76052 Office (817) 710-5233
Sales@frctexas.com • www.frctexas.com

Page 7/7

Safety Data Sheet (SDS)

Printing date 03/18/2016

OSHA Hazard Communication Standard 29 CFR 1910.1200.
Prepared to GHS Rev04.

Reviewed on April 2019

Trade name:

FX LumberGuard®

(Contd. of page 6)

DOT: US Department of Transportation IATA:

International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

SDS / MSDS Created by MSDS Authoring Services (www.MSDSAuthoring.com)

DISCLAIMER

The information in this document is believed to be correct as of the date issued.

HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE.

This information and the product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk of his use thereof.

