



Fire Retardant Coatings of Texas®, LLC
 4500 Grants Lane · Fort Worth, TX 761792
 Office (817) 710-5233 · www.frctexas.com



TECHNICAL DATA SUBMITTAL SHEET

FX Paper Guard

Fire Retardant Penetrant for Cardboard Boxes, Corrugated Board, Paper Blinds, Paper Shades, Wallpaper Coverings, Drywall, Arts & Crafts.

Testing and Standards: ASTM E84-10 Class A / Type 1, NFPA 255, ANSI/UL 723

Technical Data

FSI: <25 SL 3 Yrs <125°	375-400 Sf Per Gal. 1 Application	Environment Safe Non Corrosive	Water-Based Clear Non Toxic	Non Halogenated Do Not Let Freeze
----------------------------	--------------------------------------	-----------------------------------	--------------------------------	---

Do Not Dilute

Application Process:

Ensure that all materials to be treated are clean and dry before application. **SHAKE WELL** before and during application. Apply FX PaperGuard as it is received. Apply by spraying with a hand-pump yard sprayer at a coverage rate of 375-400 sf per gallon, depending on the material being treated. When spraying, apply FX Paper Guard until the material is damp. Drying will take 1-3 hours, depending on the air temperature at the location where you're using FX Paper Guard.

Warranty:

The use of Fire Retardant Coatings of Texas products is based on tests conducted by third-party accredited laboratories. Manufacturers and Sellers are not responsible for results where the product is used under conditions beyond their control. The manufacturer and seller's only obligation shall be to replace the quantity of the product that proves to be defective. Neither the manufacturer nor seller shall be liable for any injury, loss, or damage, direct or consequential, arising out of the use, misuse, or inability to use the product. Before using, the user shall determine the suitability of the product for his intended use and shall assume all risk and liability whatsoever in connection therewith.



WARNING: KEEP THIS AND ALL CHEMICALS OUT OF CHILDRENS REACH - AS WITH MOST PRODUCTS, THIS PRODUCT MAY CAUSE EYE AND/OR SKIN IRRITATION. ALWAYS WEAR PERSONAL PROTECTION EQUIPMENT WHEN HANDLING ANY CHEMICALS.