

Fire Retardant Coatings of Texas®, LLC

1150 Blue Mound Rd West #403 Haslet, Texas 76052 Office (817) 710-5233 Fax (817) 439-8385 www.frctexas.com



SUBMITTAL SHEET FX PaperGuard

Fire Retardant for Paper, Drywall, Cardboard Boxes, Corrugated Board, Paper Blinds, Shades, Wall Paper Coverings, Paper Faced Insulation, Paper Crafts and more.

Testing and Standards: Accredited 3rd Party Testing Laboratories ASTM E84-10 Class A / Type 1, ASTM D4727 Standards, NFPA 255, ANSI/UL 723

	Т	echnical Data		
FSI: <25	375-425 Sf Per Gal.	Environment Safe	Water Based Clear	Non Halogenated
SL 3 Yrs <125°	1 Coat Application	Non Corrosive	Non Toxic	Do Not Let Freeze
		Do Not Dilute		

Application Process:

Ensure that all materials to be treated are clean and dry prior to application. **SHAKE WELL** before and during application. Apply FX PaperGuard as it is received. Apply by brushing or spraying on with a hand pump sprayer at a coverage rate of 375-425 sf per gallon depending on material being treated. When spraying or brushing, apply FX Paper Guard just until material is damp, drying will require 1-3 hours depending on the conditions of the air (temp) in the location where you're using FX Paper Guard.

Warranty:

The use of Fire Retardant Coatings of Texas' products are based on tests conducted by third party accredited Laboratory's. Manufacturer and Sellers are not responsible for results where the product is used under conditions beyond their control. Manufacturer and sellers only obligation shall be to replace such quantity of the product proved to be defective. Neither the manufacturer nor seller shall be liable for any injury, loss or damage, direct or consequential, arising out of the use, misuse, or the inability to use the product. Before using, user shall determine the suitability of the product for his intended use and user shall assume all risk and liability whatsoever in connection therewith.





WARNING: KEEP THIS AND ALL CHEMICALS OUT OF CHILDRENS REACH HAS WITH MOST PRODUCTS, THIS MAY CAUSE EYE/SKIN IRRITATION ALWAYS WEAR PERSONAL PROTECTION EQUIPMENT WHEN HANDLING ANY CHEMICALS.